
MBC 1500/150
MB 1500/150



1.5 x 3.2 m

1500 kg

7 Persons
as transport platform

12-24 m/min

TRANSPORT PLATFORMS

GOODS HOISTS

CONSTRUCTION HOISTS

MAST CLIMBERS

MABER®
Lifting Technologies

MADE IN ITALY SINCE 1988

TRANSPORT PLATFORM: Transport platform built in line with EN16719 are used to transport goods and personell between floors. Available in different platform sizes, voltages, types of ramps, colours and speed. Possibility to choose different accessories. Customizable for specific needs.
GOODS HOIST: Builders' hoist for goods with accessible platform built in line with EN12158-1. Available in different platform sizes, voltages, types of ramps, colours and speed. Possibility to choose different accessories. Customizable for specific needs.

MODEL	UOM	MBC 1500/150		MB 1500/150
TYPE		TRANSPORT PLATFORM	BUILDERS' HOIST FOR GOODS	BUILDERS' HOIST FOR GOODS
STANDARD OF REFERENCE		EN 16719	EN 12158-1	EN 12158-1
RATED LOAD	kg	1500		1500
MAX HEIGHT	m	150		150
TIES SPACING	m	7		7
OVERHANG	m	3		3
PLATFORM WIDTH (W)	m	1.5		1.5
PLATFORM LENGTH (L)	m	3.2 *		3.2 *
PLATFORM HEIGHT (H)	m	1.1		1.1
RUNNING SPEED	m/min	12	24 **	24 **
MOTOR POWER	kW	2 x 4	2 X 8	2 X 8
MAX PERSONS	No.	7	0	0
DRIVE CONTROL	Type	DOL - DIRECT ON LINE **		DOL - DIRECT ON LINE **
SUPPLY VOLTAGE / FREQUENCY	V/Hz	THREE-PHASE 400 / 50 ***		THREE-PHASE 400 / 50 ***
STARTING CURRENT	A	90	180	180
RCD	mA	300		300
POWER SUPPLY	kVA	75	150	150

* different length available | ** VFD - Variable Frequency Drive version speed 32 m/min | *** different voltage/frequency available

Different configurations



Landing Doors/Gates

SLIDING LANDING GATE




SWIVEL LANDING GATE



MAST SECTION

W = 490 mm
L = 500 mm
H = 1495 mm

WEIGHT 91 Kg




USED IN MABER MODELS:

Transport Platform: MBC 1500/150, MBC 3500/120
Goods Hoist: MB 1500/150, MB 3500/120
Mast Climber: MBP 12-33

Technical Information

TRANSPORT PLATFORM

GOODS HOISTS



DIMENSIONS

W= 1.5 m	**L**= 3.2 m	**H¹**= 1.1 m	**H²**= 2.0 / 2.7 m
W$_B$= 3.7 m	**L$_B$**= 4.6 m	**H$_B$**= 1.1 m	

FEATURES

• Anti-collision grid • Overload detection device • Reduced 1.1 m or 2.0 m base enclosure • Emergency brake
• Falling object protection roof (mandatory for transport platform only) • Rack lubrication pump (option)
• Certified by notified body (mandatory for transport platform only) • Large 3 m “C” door (option)









Maber Hoist Srl
Via Dell'Industria e dell'Artigianato, 16
35010 Carmignano di Brenta (PD), Italy

+39 049 595 89 75

info@maber.eu

www.maber.eu